



☞ Solar Gard® Info Sheet

Accelerator

One product - many smart applications.

Key features & benefits

Window film (architectural and automotive)

During certain parts of the year there is a risk that newly installed window film and paint protection film will be exposed to very low temperatures. With the Accelerator in your mounting fluid, you will still be able to perform installations when close to freezing point.

Paint protection film

Spray Accelerator between the paint protection film and the surface you are mounting and to speed up the installation process. Quick, easy and safe!



Solar Gard® Accelerator -
quick, easy and safe!

How to use Accelerator?

- **Dosage for external film (OSW) and installation in colder temperatures:**
Add 60 ml Accelerator to 1000 ml installation mix. You may need to compensate with some extra FilmApp.
- **Dosage Clearshield Pro installation:**
Add 50 ml Accelerator to 650 ml of mounting fluid.
- **Or...**
Simply remove the nozzle from the ST0721 bottle and fix onto Accelerator bottle and spray / disperse as needed between the material and the surface to be mounted. This way you achieve effective adhesion without damaging the glue or surface that you are installing.

Order information

Product number	Content	Min. order
STEX0333	1 litre	1 bottle



Be careful when installing,
especially when...

- the glass is not at normal room temperature
(for example in garages, warehouses, etc.)



www.solargard.com/uk

Saint-Gobain Innovative Materials
Belgium SA/NV / Solar Gard
Karreweg 18, 9870 Zulte
Tel: +32 9 240 95 66
info.emea@solargard.com

PDF0333INT 11/17
© Copyright 2017, Saint-Gobain Performance Plastics and/or its affiliates
All Rights Reserved • www.solargard.com

